

jc545 U.S. PTO
02/23/00

General Motors Corporation
Legal Staff
P.O. Box 33114
Detroit, MI 48232

15-FEB-00

Box Patent Applications
Assistant Commissioner for Patents
Washington DC 20231

jc675 U.S. PTO
09/511292
02/23/00

Enclosed for filing are the following patent application papers:

Docket No. H-204325

Inventors: JAMES NAGASHIMA
TERENCE G. WARD


Title: APPARATUS AND METHOD FOR MOUNTING A POWER MODULE

Filing Fee Formula

Basic Fee	\$	690.00
Additional Fees:		
Number of independent claims in excess of 3, times \$78.00.....	\$	0.00
Number of claims in excess of 20, times \$18.00	\$	0.00
Multiple dependent claim, add \$260.00.....	\$	0.00
Total Filing Fee	\$	690.00

The patent specification H-204325 entitled APPARATUS AND METHOD FOR MOUNTING A POWER MODULE and filed in the Patent and Trademark Office herewith is the patent specification for which the inventor(s) executed the Declaration enclosed herewith.

Please charge the \$690.00 filing fee to GENERAL MOTORS CORPORATION Deposit Account No. 07-0960.


ANTHONY LUKE SIMON
Reg. No. 34434
313/974-1842

Enclosures

H-204325

APPARATUS AND METHOD FOR MOUNTING A POWER MODULE

TECHNICAL FIELD

The present invention relates generally to a method and apparatus for mounting a power module and, more particularly, to clip fasteners for securely mounting a power module to a heat sinking surface or medium.

5

BACKGROUND OF THE INVENTION

The usual hybrid power modules (HPM) in power inverter for motor drives is well known. The power modules include associated power switches and other related functions. A common method of mounting these devices is by inserting a screw in each of the mounting holes provided at each corner thereof with the screw engaging threaded holes in a chassis. These power modules generate excessive heat and therefore include a thermally conductive baseplate to dissipate the excessive heat. The baseplate is typically a metallic plate in thermal communication with the power switches of the module.

It is also known for a hybrid power module to be mounted over an opening of a fluid manifold so that liquid coolant flowing through the manifold comes into direct contact with the coolant for cooling the power module. This arrangement has the advantage of a more efficient cooling than using ambient air. The environment of the power module and/or the ambient air surrounding the power module typically does not provide efficient cooling. The baseplate of the power module is sealed to the coolant manifold by an O-ring seal to prevent coolant from leaking from the manifold. Accordingly, a consistent force across each edge of the module is desired to ensure that the O-ring does not leak over its design life and environment.

Typically, the power module is mounted to the manifold by four bolts at the corners of the power module (through the aforementioned mounting

holes). The bolts pass through respective mounting holes in the baseplate and tightened within threaded holes in the manifold. The long space between mounting holes located at the corners allows the center portion of the edge of the baseplate to deflect. This deflection can cause a leak. The base plate has
5 also been provided with a plurality of mounting holes intermediate the corner holes to prevent the deflection of the baseplate. While the additional mounting holes allow the power module to be securely mounted to the cooling manifold, this configuration increases the cost and labor to mount the power module. In addition, the intermediate mounting holes take up valuable space which could
10 be used to mount devices or reduce the size of the power module.

SUMMARY OF THE INVENTION

It is therefore, a primary object of the present invention to provide a novel apparatus and method for mounting power modules. The power
15 module is mounted over an opening of a fluid manifold so that liquid coolants flowing through the manifold comes into direct contact with the coolant for cooling the power module. As in the prior art, this arrangement has the advantage of a more efficient cooling than using ambient air. The environment of the power module and/or the ambient air surrounding the power module
20 typically does not provide efficient cooling. The power module includes a thermally conductive baseplate to dissipate the excessive heat generated during operation. The baseplate of the power module is sealed to the coolant manifold by an O-ring seal to prevent coolant from leaking from the manifold. A consistent force across each edge of the module is maintained by a plurality of
25 connecting elements to ensure that the O-ring does not leak over its design life and environment.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will now be described, by way of example
30 only, with reference to the accompanying drawings in which:

Figure 1 is an exploded view of a power module mounted to a cooling manifold embodying the present invention;

Figure 2 is a perspective view of the power module with a baseplate, a cover of the baseplate, and a manifold of Figure 1; and

5 Figure 3 is a cross sectional view of power module of Figure 2 taken along line 3.

DETAILED DESCRIPTION OF THE INVENTION

Referring to Figure 1-3, a hybrid power module assembly, 10 generally designated 10 is mounted to a cooling manifold 12 wherein liquid coolant flows. While a hybrid power module is illustrated, one skilled in the art will recognize that the present invention may apply to any electronic device that requires cooling. The hybrid power module includes electronic circuit/components thermally connected to a generally rectangular baseplate 14. 15 The baseplate 14 having an upper surface 16 and lower surface 18. The power module 10 is supported at the upper surface 16 of the baseplate 14. The manifold 12 has a top 20, a bottom 22 and sides 24 and 26 which define a channel 28 in which liquid coolant flows. A rectangular opening 30 is defined through the top 20 into channel 28 of the manifold 12. The baseplate 14 is fitted 20 onto the rectangular opening 30 in the manifold 12 with a gasket (a sealing member) 31 disposed therebetween. It will be appreciated that the gasket could be of any type, including a stamped flat gasket. An O-ring gasket requires a groove for retention which can be cast into either the baseplate or the manifold. It is noted here that the rectangular shape is only exemplary and any suitable 25 shape, preferably corresponding to the shape of the device requiring removal of heat, will suffice. Accordingly, the baseplate 14 and the opening 30 of the manifold may be of other shapes such as oval, round, or other suitable shapes. Indentations 32 are molded into sides 34 and 36 of a case 38 of power module assembly 10. Case 38 is preferably plastic and encloses the electronic circuits 30 of the power module assembly 10.

A plurality of recesses 40 are formed in sides 24 and 26 of the manifold 12. Recesses 40 are aligned with indentations 32 to position power module assembly 10 on manifold 12 over opening 30. A plurality of connecting elements 44 retain power module assembly 10 on manifold 12. In an exemplary
5 embodiment, connecting elements 44 are generally C-shaped spring clips having an elongated portion 46, an upper extension 48 and a lower extension 50. Also, these clips are preferably comprised of metal and are resilient whereby they have a spring retention force. These spring clips are preferably made using a metal stamping process, as such is well known, and provides for a low cost
10 method of manufacturing. Each of these spring clips is installed by mounting one of the extensions, e.g., lower extension 50 in a recess 40 and a force is applied to the elongated portion 46 which causes the upper extension 48 to be urged outwardly (and angled upwardly) as it pushes against the side of the case 38 of the power module assembly 10 until extension 48 enters indentations 32,
15 and snaps into place. These spring clips are uniformly distributed (located) along opposing sides of power module assembly 10, to provide a consistent force across each edge of the module.

As is best seen in Figures 2 and 3, the lower surface 18 of the baseplate 14 is in direct contact with the coolant (not shown) flowing within
20 channel 28 of the manifold 12. It is this direct contact that sinks the heat away from the power module assembly 10 during operation thereof.

An advantage of the present invention is that this method of snap fitting the spring clip into the recesses does not require additional area on the baseplate. Further, the spring clips provide consistent pressure across each
25 flange face for sealing. The clips are also low cost stampings similar to those used to clamp radiator housings together. Unlike screws or other threaded fasteners, the spring clips are self adjusting and will not loosen or back out over time. The spring clips also mitigate creep of joint materials. In addition, installation is simple since the spring clips can be accomplished by hand or with
30 simple fixturing. This method can be used with spring clips alone or in

combination with the corner mounting screws. While the immediate application is for direct liquid cooling, this invention can be used to mount modules to a standard heatsink with a thermal grease interface or the like.

5 It will be understood that a person skilled in the art may make modifications to the preferred embodiment shown herein within the scope and intent of the claims. While the present invention has been described as carried out in a specific embodiment thereof, it is not intended to be limited thereby but is intended to cover the invention broadly within the scope and spirit of the claims.

CLAIMS

1. A cooling assembly comprising:
a heat sinking member having a plurality of recesses defined therein;
a power module disposed on said heat sinking member, said
5 power module having a casing with pluralities of indentations therein, said indentations being positioned relative to said recesses to locate said power module on said heat sinking member; and
a plurality of spring clips, each of said spring clips having first and second extensions, one of said first and second extensions cooperating with
10 a corresponding one or said recesses and the other one of said first and second extensions corresponding with a corresponding one or said indentations to retain said power module on said heat sinking member and to facilitate heat transfer during operation of said power module.
2. The cooling assembly of claim 1, further comprising a sealing member.
3. The cooling assembly of claim 2, wherein the sealing member is a gasket.
4. The cooling assembly of claim 4, wherein the said heat sinking member includes a channel defined therein for allowing coolant to flow therethrough.
5. The cooling assembly of claim 4, wherein the heat sinking member includes an opening leading to said channel to allow said power module to directly contact coolant flowing in said channel.

6. The cooling assembly of claim 1 wherein said heat sinking member is an elongated generally rectangular member.

7. The cooling assembly of claim 5, wherein said opening is generally rectangular.

8. The cooling assembly of claim 5, wherein said power module includes a baseplate sealably mounted over said opening.

9. The cooling assembly of claim 1, wherein said spring clips comprise generally C-shaped spring clips.

10. A method of assembling a cooling assembly system, comprising:

locating a power module on a heat sinking member receptive to coolant flow therethrough; and

5 coupling said power module and the heat sinking member using a plurality of spring clips.

11. The method of assembly of claim 10 further comprising:
locating a sealing member between said power module and said heat sinking member.



H-204325

APPARATUS AND METHOD FOR MOUNTING A POWER MODULE

ABSTRACT OF THE INVENTION

A power module with heat sources wherein the heat is dissipated by a heat sink. The heat sink includes a manifold with coolant flowing therein. An opening on the manifold enables the coolant to come in direct contact with a
5 base plate of the power module. The power module being retained on the heat sink by a plurality of spring clips.






FIG. 1





FIG. 3

**DECLARATION
and
DESIGNATION OF CORRESPONDENCE ADDRESS**

As an inventor named below, I hereby declare that:

My residence, post office address and citizenship are stated below next to my name.

I believe I am the original, first and sole inventor (if only one inventor is named below) or an original, first and joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought in the specification H-204325 entitled

APPARATUS AND METHOD FOR MOUNTING A POWER MODULE

I have reviewed and understand the contents of the above-identified specification including the claims, as amended by any amendment referred to in this Declaration.

I acknowledge my duty to disclose to the Patent and Trademark Office all information known to me to be material to patentability as defined in title 37 Code of Federal Regulations, Section 1.56.

I further declare that all statements made above of my own knowledge are true, that all statements made above on information and belief are believed to be true, and that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under title 18 United States Code, Section 1001 and may jeopardize the validity of the application or any patent issuing thereon.

Address all communications to: ANTHONY LUKE SIMON
General Motors Corporation
Legal Staff
P.O. Box 33114
Detroit, MI 48232

Telephone: 313/974-1842

Inventor's signature



Date 1/28/00

Full name :

JAMES NAGASHIMA

Citizenship: US


Residence :

CERRITOS, CA

Post office address:

16608 MOORBROOK AVENUE
CERRITOS, CA 90703

Inventor's signature



Date 1/27/00

Full name :

TERENCE G. WARD

Citizenship: US

Residence :

REDONDO BEACH, CA

Post office address:

1612 HERRIN STREET
REDONDO BEACH, CA 90278

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Docket No. H-204325

Inventors: JAMES NAGASHIMA
TERENCE G. WARD

Title: APPARATUS AND METHOD FOR MOUNTING A POWER MODULE

**POWER OF ATTORNEY AND
DESIGNATION OF CORRESPONDENCE ADDRESS**

As an agent of General Motors Corporation, General Motors of Canada Limited, General Motors Japan Ltd., General Motors Strasbourg S.A., and Saturn Corporation, one or more of whom is the assignee of this patent application, I hereby appoint the following attorney employed by General Motors Corporation to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

ANTHONY LUKE SIMON (Reg. No. 34434)

Address all communications to:

ANTHONY LUKE SIMON
General Motors Corporation
Legal Staff
P.O. Box 33114
Detroit, MI 48232
Telephone: 313/974-1842

I am authorized to make the above appointment. The assignee's ownership of this patent application is established by the attached assignment documentation, the attached documentation is a true copy of the original documentation, and the original or a true copy of the attached documentation has been or is concurrently being submitted to the Patent and Trademark Office for recording.


By:



Name: Dean L. Ellis Agent

Date: February 15, 2000

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Scanned copy is best available.

NO TRANSMITTAL ENCLOSED